

PART NUMBER: LTD151  
REVISION: D

MODEL NO.	MOTOR	RPM	MAX VAC		MAX PRESS.		HP	KW	NET WT.	
			"H <sub>2</sub> O"	mbar	"H <sub>2</sub> O"	mbar			lbs.	kg
R6350A-2	190-220/380-415-50-3	2850	70	174	78	194	4.8	3.6	112	50.8
	208-230/460-60-3	3450	88	219	105	262	5	3.7		

NOTES:  
1. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.  
2. WIRING DIAGRAM: SEE MOTOR.

PERFORMANCE DATA  
THE PERFORMANCE DATA SHOWN WAS DETERMINED UNDER  
THE FOLLOWING CONDITIONS:


LINE VOLTAGE @ 60 Hz. 230V OR 460V FOR 3 PHASE UNITS.  
115V OR 230V FOR 1 PHASE UNITS.

LINE VOLTAGE @ 50Hz, 220V FOR 3 PHASE OR 1 PHASE UNITS.  
UNITS IN A TEMPERATURES STABLE CONDITION.

DELIVERY MEASUREMENTS MADE WITH OUTPUT PORT THROTTLED.

TEST CONDITIONS: INLET AIR DENSITY @ 0.075 lbs. PER cu. ft.  
[20°C (68°F), 29.92" Hg (14.7 PSIA)].

NORMAL PERFORMANCE VARIATIONS ON THE RESISTANCE CURVE WITHIN  $\pm 10\%$  OF SUPPLIED DATA CAN BE EXPECTED



\* = RECOMMENDED MAXIMUM DUTY  
mm / inches

